

Hardware Compatibility

Most Popular Torque Wrenches - Snap-on CONTROLTECH™

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
Snap-on	CTECHW2MR240S	1.5-27 (1-20)	Fixed Ratchet	3/8"
Snap-on	CTECHW1MR240S	1.5-27 (1-20)	Fixed Ratchet	1/4"
Snap-on	CTECHW2F100AS	7-135 (5-100)	Flex Head	3/8"
Snap-on	CTECHW2M1200S	7-135 (5-100)	Fixed Ratchet	3/8"
Snap-on	CTECHW3F250AS	17-340 (12.5-250)	Flex Head	1/2"
Snap-on	CTECHW4R650AS	32.5-650 (24-480)	Fixed Ratchet	3/4"

Most Popular Micro Torque Screwdrivers - Snap-on CONTROLTECH™

Manufacturer	Model	Range in-lb	Drive Size	Type
Snap-on	CTECHWMS80MS	4-80	1/4" Square	Male
Snap-on	CTECHWMS80FS	4-80	1/4" Hex	Female

Snap-on CONTROLTECH™ Bluetooth Digital Micro Torque Wrenches

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
Snap-on	CTECHW1MR100S	0.57-11.30 (0.42-8.33)	Fixed Ratchet	1/4" Square Ratchet
Snap-on	CTECHW2MR100S	0.57-11.30 (0.42-8.33)	Fixed Ratchet	3/8" Square Ratchet
Snap-on	CTECHWANM30S	1.5-30 (1.11-22.13)	Interchangeable	IZO/ISO (9 x 12 mm)
Snap-on	CTECHWJM300S	1.7-34 (1.25-25)	Interchangeable	J (0.425")
Snap-on	CTECHW1MR240S	1.36-27.12 (1-20)	Fixed Ratchet	1/4" Square Ratchet
Snap-on	CTECHW2MR240S	1.36-27.12 (1-20)	Fixed Ratchet	3/8" Square Ratchet
Snap-on	CTECHW2R100AS	6.8-135.6 (5-100)	Fixed Ratchet	3/8"
Snap-on	CTECHW2M1200S	6.8-135.6 (5-100)	Fixed Ratchet	3/8"
Snap-on	CTECHW2F100AS	6.8-135.6 (5-100)	Flex Head	3/8"
Snap-on	CTECHW2F100B	6.8-135.6 (5-100)	Flex Head w/Ingress Protection	3/8"
Snap-on	CTECHWYM1200S	6.8-135.6 (5-100)	Interchangeable	Y (0.560")
Snap-on	CTECHWANM135S	6.8-135 (5-99.6)	Interchangeable	IZO/ISO (9 x 12 mm)

Hardware Compatibility

Snap-on CONTROLTECH™ IS/EX Bluetooth Digital Torque Wrenches

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
Snap-on	CTECHW1UA135	6.8-135 (5-99.6)	Interchangeable	IZO/ISO (9X12mm)
Snap-on	CTECHW1UB400	20-400 (14.8-295)	Interchangeable	IZO/ISO (14X18mm)
Snap-on	CTECHW1UR650	33-650 (24-479.4)	Fixed Ratchet	3/4" Square Ratchet

Snap-on CONTROLTECH™ Bluetooth Digital Torque Wrenches

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
Snap-on	CTECHWY100AS	6.8-135.6 (5-100)	Interchangeable	Y (0.560)
Snap-on	CTECHWAN135AS	6.8-135 (5-99.6)	Interchangeable	IZO/ISO (9 x 12 mm)
Snap-on	CTECHW3F250AS	16.9-339 (12.5-250)	Flex Head	1/2"
Snap-on	CTECHW3R250AS	16.9-339 (12.5-250)	Fixed Ratchet	1/2"
Snap-on	CTECHW3R250B	16.9-339 (12.5-250)	Fixed Ratchet w/Ingress Protection	1/2"
Snap-on	CTECHWX250AS	16.9-339 (12.5-250)	Interchangeable	X (0.735)
Snap-on	CTECHWBN340AS	17-340 (12.5-250.8)	Interchangeable	IZO/ISO (14 x 18 mm)
Snap-on	CTECHW4R650AS	32.5-650 (24-479.5)	Fixed Ratchet	3/4"
Snap-on	CTECHWZN650AS	32.5-650 (24-479.5)	Interchangeable	Z (0.560)
Snap-on	CTECHW4R600AS	40.7-813.5 (30-600)	Fixed Ratchet	3/4"
Snap-on	CTECHWZ600AS	40.7-813.5 (30-600)	Interchangeable	Z (0.560)

Norbar Protonic Plus Bluetooth Digital Torque Wrenches

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
Norbar	130512	5-100 (3.7-73.5)	Fixed Ratchet	3/8"
Norbar	130513	5-100 (3.7-73.5)	Fixed Ratchet	1/2"
Norbar	130514	10-200 (7.4-147.5)	Fixed Ratchet	1/2"
Norbar	130515	17-340 (12.6-250.7)	Fixed Ratchet	1/2"
Norbar	130516	40-800 (29.5-590)	Fixed Ratchet	3/4"

Hardware Compatibility

Bahco Digital Torque Wrenches

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
 BAHCO	TAWMB930M	1.50-30 (1.11-22.13)	Interchangeable	9x12 ISO Shank
 BAHCO	TAWMB9135M	6.8-135 (5-99.5)	Interchangeable	9x12 ISO Shank
 BAHCO	TAWMB14340	17-350 (12.5-250.8)	Interchangeable	14x18 ISO Shank
 BAHCO	TAWMB24650	32.5-650 (24-479.4)	Interchangeable	24x32 ISO Shank
 BAHCO	TAWMB24800	40-800 (29.5-590)	Interchangeable	24x32 ISO Shank

Chicago Pneumatic eTorque Torque Wrenches

Manufacturer	Model	Range Nm (ft-lb)	Head Type	Drive Size
 Chicago Pneumatic	CP8916TC/8941089161	20-200 (15-147.5)	Interchangeable	1/2"
 Chicago Pneumatic	CP8918TC/8941089181	34-340 (25-250)	Interchangeable	1/2"

Bluetooth Torque Screwdrivers

Manufacturer	Model	Range	Drive Size	Type
 Snap-on	CTECHWMS80MS	4-80 in-lb	1/4" Square	Male
 Snap-on	CTECHWMS80FS	4-80 in-lb	1/4" Hex	Female
 Torbar	13054	4-80 in-lb	1/4" Hex	Female
 BAHCO	TASMB14H09	4-80 in-lb	1/4" Hex	Female

Hardware Compatibility

Hytorc Electric Torque Tools

Manufacturer	Model	Range ft-lb	Weight lbs.	Drive Size
HYTORC®	LST-0700	150-700	11.7	3/4" Square
HYTORC®	LST-1200	200-1200	12	3/4" Square
HYTORC®	LST-2000	325-2000	16.6	1" Square
HYTORC®	LST-3000	500-3000	17.7	1" Square
HYTORC®	LST-5000	800-5000	22.4	1 1/2" Square
HYTORC®	LIONGUN-.25-BSM	25-250	7.3	1/2" Square
HYTORC®	LIONGUN-.7-BSM	70-700	8.3	3/4" Square
HYTORC®	LION GUN X 1000	250-1000	9.6	3/4" Square
HYTORC®	LION GUN X 3000	600-3000	15.5	1" Square

Chicago Pneumatic Electric Torque Tools

Manufacturer	Model	Range ft-lb	Weight lbs.	Drive Size
 Chicago Pneumatic	CP8603C*	50-240	9.0	3/4" Square
 Chicago Pneumatic	CP8609C*	185-665	12.5	1" Square
 Chicago Pneumatic	CP8613C*	220-960	11.7	3/4" Square
 Chicago Pneumatic	CP8626C*	520-1910	15.9	1" Square
 Chicago Pneumatic	CP8641C*	740-3020	25.1	1" Square
 Chicago Pneumatic	CP8681C*	1470-5970	36.4	1-1/2" Square

*Note: Compatible variants include models ending in -C, -CQ, and -TC. Standalone models are not Bluetooth-enabled.

Hardware Compatibility

Hydraulic Tools

By retrofitting a customer's hydraulic pump with an available Bluetooth pressure gauge, Cumulus enables compatibility with any hydraulic tools on the market. Brands we commonly integrate with include:



Bluetooth Pressure Gauges for Hydraulic Torquing, Tensioning and Pressure Test

Manufacturer	Model	PSI Range
	CPG-1500	0-150,000 psi
	680A	0 - 60,000 psi
	681A	0 - 60,000 psi
	685	0 - 60,000 psi

Electrical Testing - Megger Insulation Resistance Testers

Manufacturer	Model	Type
Megger.	MIT525/2 (1016-086) Ver. 2	5 kV
Megger.	MIT1025/2 (1016-096) Ver. 2	10 kV
Megger.	MIT1525/2 (1016-101) Ver. 2	15 kV
Megger.	DLRO2X (1013-795)	Low Resistance Testing

Some brands available only in select markets. Please contact support@cumulusquality.com for the recommended configuration options for your respective use case before purchasing.